

ENIGMA[®]

POCKET DOORS

Sliding Gear Set SG01

SEL-PRT-02648 | Rev. 1

Part 2 Enhancement Installation

SUITABLE FOR
EI30 Concealed Frame
EI30 Shadow-Gap
EI30 Visible Trim
NFR Shadow-Gap
NFR Visible Trim



SG01 COMPONENTS



This guide is to be used in conjunction with the specified Pocket Door Frame and Trim installation guides.

Familiarise yourself with components included. All fixings will come pre-packaged to suit your specific project requirements.



INSTALLING THE WHEELS

Please ensure the securing nut is attached to the Bolt.

Wind the **Roller Bolts into the Wheels** several turns, then slide into the **Track** as shown.

Adjust the Bolts so that they are approximately **20mm** below the track.



FIT HEAD BRACKETS

Fit the **Head Brackets**, **150mm** from the edge of the Door leaf to the **centre** of the Bracket.

Ensure both Brackets are the same way up. Use **Type-03 Screws**.



HANG THE DOOR

Hang the door on the Brackets as shown (rear of the Door followed by the front).

Wind the Nuts down by hand to **temporarily hold the Door in place**. This can be finally adjusted later.

halo
assist

For help and advice with your installation contact our technical team:

Installation support **020 3880 0339**

Email sales@enigmapocketdoors.com

