

Sliding Gear Set SG02

SEL-PRT-02649 | Rev. 1

Part 2 Enhancement Installation



SG02 COMPONENTS



This guide is to be used in conjunction with the specified Pocket Door Frame and Trim installation guides.

Familiarise yourself with components included. All fixings will come pre-packaged to suit your specific project requirements.



FIX HEAD BRACKET CHANNELS

Using the plastic end cap as a spacer (front Channel only), fit the **Head Bracket Channels** flush with the edge of the Door into the rebates provided, fix using **Type-03 Screws**.

The longer Bracket is to be used towards the **front** of the Door.



PREPARE THE HANGING BRACKETS

If the Bolts have been supplied with Nuts then these need to be removed as the Nuts are not needed for this kit.

Force the **Hanger Bolt** into the **Gear Bracket** using a mallet or hammer. This will hold the Bolt captive in the Bracket, then wind several turns into the Trolley and insert into the Track.



HANG THE DOOR

A. Slide the rear Bracket into the head of the Door, fix through the bottom holes with two **Type-02** Screws.

B. Slide the front Bracket into place and tighten the hex-head Bolt. Fit the Bracket end cap (can be removed and refitted for painting).

Ensure the Door is **plumb and level**. To adjust the heights, remove the Brackets and rotate them clockwise to raise, anti-clockwise to lower.



For help and advice with your installation contact our technical team:

Installation support **020 3880 0339**
 Email sales@enigmapocketdoors.com

