



## Enigma

Generated on 30.11.2017

### Detailed description

44 mm thick top hung manually operated straight sliding system. All systems supplied with aluminium running track, running gear and metal cavity cassette with door guide and timber, metal or glass leaves or panels.

### Features and benefits:

- Cavity is formed in wall into which door/panel slides.
- Often used to save space.
- Suitable for 30-minute fire rated applications. Maximum door sizes apply.
- Rapid, economic installation.
- Choice of size. Specials available.
- Suitable for timber and glass leaves and panels.
- Doors and panels supplied in different range of finishes.
- Supplied by manufacturer in complete kit.
- Doors and panels up to 140 kg, up to 250 kg on specials.
- Door/panel width (maximum): 1650 mm. Fire rating maximum sizes apply.
- Door/panel height (maximum): 2850 mm. Fire rating maximum sizes apply.

### Product guidance - As Standard

#### Door panel thickness:

44 mm.

#### Cavity cassette:

94 mm.

### Options

#### Door leaf size:

##### - Non fire-rated:

- Height (maximum): 2850 mm.
- Width (maximum): 1650 mm.

##### - FD30:

Varies dependent on height and width of door required - consult manufacturer and insert requirement.

#### Door leaf weight (maximum):

SELO



SELO

K2

Kents Hill

Business Park

Timbold Drive

Milton Keynes

MK7 6TT

Tel: +44 (0)20 3880 0339

[www.selo-uk.com](http://www.selo-uk.com)

[sales@selo-uk.com](mailto:sales@selo-uk.com)



140 kg.

#### Accessories:

- Flush pull set, circular- CFP01: 70 mm diameter, stain stainless steel.
- Flush pull set, oval - OFP01: 135 mm long, stain stainless steel.
- Flush pull set, rectangular- RFP01: 135 mm long, stain stainless steel.
- Flush pull set, square - SFP01: 60 x 60 mm, stain stainless steel.
- Thumb turn locking set - ELS01 and ELS02: stain stainless steel.

Other options are available, consult manufacturer for more information.

### Product specification

#### Manufacturer

- Name: SELO
- Web: [www.selo-uk.com](http://www.selo-uk.com)
- Email: [sales@selo-uk.com](mailto:sales@selo-uk.com)
- Tel: +44 (0)20 3880 0339
- Fax: +44 (0)845 241 6896
- Address: K2 Kents Hill Business Park, Timbold Drive, Milton Keynes. MK7 6TT

**Product reference**      Selo Enigma

#### Door leaf

- Configuration      Single leaf, soft close  
Single leaf, soft close and open  
Double leaf, soft close  
Double leaf, soft close and open  
Double leaf, simultaneous opening/  
closing - Not applicable for non fire-rated  
concealed kits.

- Size (w x h)      [ \_\_\_\_\_ ]

#### Construction/ Finish

- Stud      Glass  
Aluminium, unfinished - For site painting.  
Aluminium, powder coated - Insert colour  
requirement.  
Timber, primed - For site finishing.  
Timber, pre-painted - Insert colour  
requirement.
- Door leaf      Timber, paint grade - For site finishing.  
Timber, pre-painted - Insert colour  
requirement.

SELO



Timber, wood veneer - Insert requirement.  
Timber, laminate - Insert requirement.

**Wall depth**

120 mm - Standard (1no 12.5  
plasterboard each side).  
145 mm - Standard (2no. 12.5  
plasterboard each side).  
Bespoke - Insert requirement.

**Frame type**

Concealed - Metal trims for a fully  
concealed finish.  
Shadow gap - Timber trims to form  
shadow gap detail.  
Visible - Timber trims for fixture of an  
architrave.

**Accessories**

[None]  
[Flush pull set, circular- CFP01] - Includes  
finger end pull to leading edge.  
[Flush pull set, oval - OFP01] - Includes  
finger end pull to leading edge.  
[Flush pull set, rectangular- RFP01] -  
Includes finger end pull to leading edge.  
[Flush pull set, square - SFP01] - Includes  
finger end pull to leading edge.  
[Touch latch mechanism - TL130]  
[Thumb turn locking set - ELS01] - Non  
fire-rated.  
[Thumb turn locking set - ELS02] - FD30.